

## D55 High Definition Mini Speed Dome



### Features

- ◆ Integrated and handle fast installation
- ◆ Built-in heating and radiating system, 4 alarms input, 1 alarm output as factory default, IP board is optional.
- ◆ Built-in zoom with 120 times(10x optical, 12x digital).
- ◆ Resolutions: 500TVL/570TVL(optional); Min Illumination: color 0.015Lux, B&W 0.0004Lux
- ◆ Pan 360°, Tilt 90°continuously rotation with auto-flip, humanize focus and speed proportion.
- ◆ 128 presets(titles can be set), 4 tours; 8 programmable zones(titles can be set); 4 pattern, each record time is more than 180 seconds; 4 scan, support camera scanning repeatedly between right limit and left limit at anappointed speed.
- ◆ Built-in OSD menu, can change information and parameter of dome through menu, also can set and call presettscan, pattern, camera mode and display name etc.
- ◆ Park action function, can auto-call presets or start-up tour, pattern, scan and display areas after dome is idle for of time.
- ◆ Communications: RS485
- ◆ Built-in TVS1500W lightning-proof, surge-proof and wave-proof, IP66 all-day defend cover.

### Specification

Supported module	SONY EX20 (SONY EX11, SONY H11, SAMSUNG SDM100 Optional)
Scanning system	PAL : 2:1 interlacing
Imaging element	1/4 inch Super HAD CCD
Significant pixel (H×V)	752(H)X582(V)
Resolution	500TVL / 570TVL (Optional)
Video output	1.0±0.2Vp-p
S/N ratio (S/N)	≥50dB
Illumination	Color 0.015Lux
White balance	Auto/manual (R/B gain control)
Back-compensation	Off/auto
Focus	5.1mm ~51mm
Electron Shutter	1/1 ~ 1/10,000s
Manual speed	Pan (0.5°~160°/s) Tilt (0.5°~90°/s)
Preset speed	320°/s
Rotation	Continuously 360° ; tilt 0~90° with auto-flip
Speed Proportion	As the length of focus, to auto-adjust the speed
Zoom	Total zoom 120X (Optical 10X, Digital 12X )
Preset	128 preset, title can be edited
Auto-flip	Tilt down 90°, with auto-flip 180°
Scan	355°programmable , 4 scans
Display zone	8 programmable zones with titles
Sync model	Internal
Decoder	Built-in
Video output	Female BNC
Remote controlling	RS485
Baud rate (RS485)	2400 / 4800 / 9600/19200 bps
ID range	1~255
Temperature	0°C~+50°C
Humidity	0~90% (No condensation)
Protection grade	IP66, 1500w lightning-proof, surge-proof, all-day defend cover
Power supply	AC 24V
Power consumption	< 12W
Net weight/Gross weight	1.5Kg/2.5Kg
Dome Dimension (L*W*H)	154*154*152.6 mm
Carton Dimension (L*W*H)	322*202*212 mm



### K.S.R. ELECTRONICS CO., LTD.

1072 Lardphao Rd., Samsenok, Huaykwang, Bangkok 10320  
 Tel : 0-2939-8383 Fax : 0-2513-6040  
 email : ksrelectronics@yahoo.com