

DS-7204HVI-S Standalone DVR



Key Features

- Each channel supports up to 4CIF encoding
- Dual streams
- VGA output
- 1 SATA interface
- Support main and auxiliary video output

Specifications

Video/Audio Input		Hard Disk Drive	
Video Compression	H.264	Interface	SATA x 1
Video Input	4 Ch	Capacity	Each HDD Supports Up to 2000GB
Video Input Interface	BNC (1.0Vp-p, 75Ω)		
Audio Compression	OggVorbis, 16Kbps		
Audio Input	1 Ch		
Audio Input Interface	RCA (2.0~2.4Vp-p, 1KΩ)		
Intercom	1 Ch (Audio Input)		
Video/Audio Output		External Interface	
Display	PAL: 704x576 NTSC: 704*480	Communication Interface	1 RJ45 10M/100M Ethernet Port
Recording Resolution	QCIF/CIF/2CIF/DCIF/4CIF	RS-485 Port	1 (T+, T-, R+, R-)
Main Video Output	1 Ch, BNC (1.0Vp-p, 75Ω)	USB Interface	1
Aux Video Output	1 Ch, BNC (1.0Vp-p, 75Ω)	Alarm Input	4 (Terminal Block)
Video Loop Output	4CIF: 6fps	Alarm Output	1 (Terminal Block)
Recording/Playback	DCIF: 12fps 2CIF: 15fps CIF: 25(P)/30(N)fps	General	
Audio Output	1 Ch, RCA (2.0~2.4Vp-p, 600Ω)	Power Supply	12VDC
Dual Streams	Yes	Power Consumption	≤40W (w/o HDD or DVD-R/W)
Bit Rate	32Kbps ~ 8Mbps	Operating Temperature	-10°C ~ 55°C
VGA Output	1 (Support 1024x768/60Hz)	Humidity	10% ~ 90%
		Dimensions	315mm(W)x230mm(D) 45mm(H)
		Weight	≤2.8Kg (w/o HDD or DVD-R/W)

