

DS-9016HFI-S Intelligent Hybrid DVR



Key Features

- H.264 video compression
- 3 independent local video output (VGA, MAIN and AUX video/audio out)
- Up to 32 simultaneous users
- Pentaplex operations enables simultaneous recording, live view, playback, back-up and network operations
- Advanced motion detection and video analytics
- Easy back-up to USB and optical drives
- Support up to 8 SATA hard disk drives

Specifications

Video/Audio Input		Hard Disk Drive	
Video Compression	H.264	Interface	SATA (Up to 8) Each HDD Supports Over 2TB
Video Input	Up to 16 Ch Analog and 8 Ch IP		
Audio Compression	OggVorbis	Capacity	
Audio Input	16 Ch, BNC (2Vp-p, 1kΩ)	External Interface	
Intercom Input	2, BNC (2Vp-p, 1kΩ)	Network Interface	1, RJ45 10M/100M/1000M Ethernet Port
Video/Audio Output		Serial Interface	1xRS-232, 1xRS-485 (PTZ),
Display Resolution	PAL: 704x576 Pixels NTSC: 704x480 Pixels	USB Interface	1xRS-485 (Keyboard Interface) 2xUSB2.0
VGA Output	1x1024x768 (60Hz), 1x1024x768 (70Hz), 1x1280x1024 (60Hz)	Alarm Input	16 (Terminal Block)
Recording Resolution	720P/4CIF/DCIF/2CIF/CIF/QCIF	Alarm Output	4 (Terminal Block)
Video Output	2 Ch, BNC (1.0Vp-p, 75Ω)	General	
Frame Rate	PAL: Up to 25fps NTSC: Up to 30fps	Power Supply	100~240VAC, 6.3A, 50~60Hz
Video Bit Rate	32Kbps~6144Kbps	Power Consumption	28W (w/o HDD)
Audio Output	2 Ch, BNC (Linear Electric Level, 600Ω)	Operating Temperature	-10°C ~ 55°C
Audio Bit Rate	16kbps	Humidity	10% ~ 90%
		Chassis	19" Standard 2U
		Dimensions	450mm(D)×450mm(W) ×95mm(H)
		Weight	≤8 Kg (w/o HDD)

